

VORTEX S WTG Harness QC, Steel Chest

H34Q2

Lightweight multi-purpose harness with integrated belt. Specifically designed with steel chest attachment point for the renewables industry.

Features:

- High rear attachment point and steel chest attachment point
- Integrated work positioning belt with side D's
- Low profile breathable back panel and waist pad
- Plastic wear protection in key areas
- Rapid fitting for emergency evacuation
- Contoured fit for comfort and freedom of movement
- Quick connect leg loop and chest buckles
- Integral lanyard parking points

Rear attachment point is positioned at nape of neck to eliminate discomfort when climbing WTG interior ladders. This ensures more vertical orientation of casualty when being lowered during rescue and minimises interference with ladder rungs.

Steel chest attachment point for compatibility with specific fall arrest guided rail and wire systems. Compatibility statement available for HACA 7400 and Latchway 3102L-00 and 3100L-00AC fall arrest runner systems.

Breathable back panel and padded waist belt provide support and protection while climbing. Padded waist belt has side D's for work positioning. The back panel also helps to hold the harness in shape so reduces tangling and aid orientation.

SafeLock[™] quick connect leg, waist and chest buckles make fitting fast and easy. Quick connect buckles also allows the harness to be removed without the need for re-adjustment.

Shoulder buckles allow quick and easy adjustment with one hand making the harness easily adjustable for offshore use. Elastic webbing retainers on strap ends allow slack webbing to be stowed neatly and easily.

Chest rings align the webbing to ensure a good fit with maximum comfort and security. Back panel is low profile to prevent snagging.

Integrated parking points allow lanyards to be stowed when not in use yet break free in a fall preventing issues from incorrect loading. These are positioned on the shoulder pads to avoid the trip hazard associated with longer lanyards.

Harness complies with Siemens PPE requirements PRO-13838 Ap1


Patented

90032940240001

Specifications:

NB: specifications and colour may change without notice.

Size: Standard or Large

EN Test Mass: 140kg

Loading: fall arrest loads

Conformity: EN 361, EN 358

Materials: Polyamide, Stainless Steel & Aluminium.

Weight (kg): 2.00

Industries: Wind

Attachment Points:

 Sternal
 Dorsal
 Lateral

Harness Measurements (cm):

Torso	78-106
Waist	80-125
Thigh	65-105

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com

heightec.com

PDS1384

22/06/22