

POWERLOCK rescue descender

D321

Rescue descender specifically designed for 2 person "pick-off" descent up to 275kg

Features:

- Specifically designed for pick off rescue
- Double-braking mechanism
- High, 275kg load capacity
- All component parts visible
- Stainless steel friction surfaces

Very fine control with minimal "Go" position for maximum safety.

The "tail" rope can be pulled back through the device if needed, to remove slack or allowing the device to move back up an unloaded rope.

Locks if handle is released or squeezed too hard.

Suitable for 2 person loads.

In addition to the EN standard approval tests the POWERLOCK (D321) has also passed the EN12841C dynamic (drop) test with 275kg.

Patented duo brake mechanism increases friction under heavy loading and reduces rate at which friction is released.

Inspection and cleaning is simple as all component parts of device are visible and accessible.

Stainless steel friction surfaces for reduced wear and consistent performance.

Available in TowerPack - Tower Rescue System (WK33)



Patented GB 2 367 048

Specifications:

NB: specifications and colour may change without notice.

Size: 11mm rope

EN Test Mass: 200kg/275kg

Loading: 200kg SWL. 2kN WLL

Conformity: EN341:1992 (Type B), EN12841:2006 (Type C)

Materials: Anodised Aluminium Alloy, Stainless Steel

Weight (kg): 0.55

Industries: Tower Rescue, Rope Rescue

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com

heightec.com

PDS104

10/02/22