

HURRICANE rope clamp w pulley, alloy

D431

**Allows creation of a quick and simple pulley system at any point along a kernmantel rope.
Key component of RescuePack casualty recovery systems.**

Features:

- Simplifies complex rigging
- Self locking catches
- X-Cam technology

The simplicity and compactness of the Hurricane is a major advantage in allowing non-experts to achieve the lifting of a suspended casualty. It is the only product to allow intuitive assembly of such a system.

Because the device can be attached at any point along the rope, the lifting system can be remote from the casualty, reducing the amount of rope required by around 70%.

X-cam has a more advanced tooth design than traditional cams and is more suitable for industrial applications as it does not pluck the rope, so reducing rate of rope wear.

- Does not jam, even against knots
- Provides high degree of grip on ropes of varying condition including after rupture of sheath

British Safety Industry Federation innovation award winner.

Available in:

- RescuePack - WK32
- Rescuepack Pro - WK35



Patented

Specifications:

NB: specifications and colour may change without notice.

Size:	10.5-12 mm rope
EN Test Mass:	n/a
Loading:	200kg SWL. 2kN WLL
Conformity:	EN12278:2007, EN12841:2006(B)
Materials:	Anodised Aluminium Alloy, Stainless Steel Cam, Nylon
Weight (kg):	0.33
Industries:	Fire and rescue service, rescue after a fall, construction, renewables, telecoms.

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com

heightec.com

PDS111

05/02/24