

RescuePack ROTOR TC, 50m**WK39050****Self contained rescue system for self-evacuation or recovery of a casualty from tower cranes**

Designed to allow automatic self-evacuation giving limited maximum descent speed, or allow the controlled rescue of a casualty from a tower crane cab, jib or ladder by lowering or lifting.

This kit complies with the Construction Plant-hire Association (CPA) Good Practice Guide regarding rescue from Tower Cranes (TCIG 2101).

The locking extendable rescue pole extends up to 3.5m and allows immediate connection to the harness of a person hanging suspended after a fall.

High strength pole and heavy duty design is rigid when fully extended, with sturdy locking mechanism and unique quick release bracket.

This method of casualty attachment does not rely on being able to clip a specific attachment ring on the casualty - which may be difficult if an energy absorber has extended to its full length.

The pole is non-conductive

The pulley provides mechanical advantage to raise a load or deviate a rope.

Includes the ultra compact, universal sized, casualty harness. Lightweight and easy to fit to an incapacitated casualty.

This compact system comes complete with durable KARI bag.

Kit includes:

- Rotor CRD x 1
- 9.5mm CRD Rope x 1
- Delta casualty harness x 1
- Rescue reach pole x 1
- Rescue pulley x1
- Throwline, 50m x 1
- Sling, nylon protected 120cm x 2
- Oval karabiner x 3
- Oval captive karabiner x 1
- Pear screwlink x 1
- Rescue kit bag x 1

Available in 50m or 100m.



Patented GB2515341

NB: specifications and colour may change without notice.

Specifications:

Size: 50m

EN Test Mass:

Loading:

Conformity: Various EN Approvals

Materials: Various

Weight (kg): 15.00

Industries: Tower Crane, Construction

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com

heightec.com

PDS380

22/01/24