

CORE twin l'yrd - 1.25m, s.hooks

L2B125S

Basic range of energy absorbing lanyards.

Features:

- Range of connectors and lengths
- Single and twin leg options
- High load rating, approved for users up to 140kg
- Unique serial ID number

Kernmantle rope legs. Twin versions interlocked preventing issues caused by 3 way loading.

Approved for users up to 140 kg.

Absorber will not deploy at force less than 200 kg. Min. strength 1500 kg after deployment.

All products have unique serial ID number allowing easy management of equipment portfolio.

Code	Legs	Harness Connector	Length ***cm	Anchorage Connector
L2B125S	2	Delta	125	Scaff hook
L1B175K	1	Oval	175	Twistlock
L1B175S	1	Oval	175	Scaff hook



Specifications:

NB: specifications and colour may change without notice.

Size: 1.25m, 1.75m

EN Test Mass: 100kg

Loading: Additionally tested 140kg Fall factor 2

Conformity: EN354:2010, EN355:2002, EN362:2004

Materials: Polyester / polyamide webbing. Stainless steel ring with alloy connectors.

Weight (kg): 1.30

Industries: Telecoms, utilities, fire and rescue service, renewables industry.

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable