

## Rescue hook with safety lock

**CH01AM**

### Alloy scaffold hook modified for rescue

#### Features:

- Main body anodised aluminium alloy
- Gate stainless steel
- Double action gate
- Gate opening: 62mm
- Overall Size: L 238mm, W 114mm
- Captive eye
- Modified gate with rescue safety lock

Aluminium Alloy body for reduced weight.

Anodised for corrosion protection.

Stainless steel gate for strength.

Double action gate is self closing and locking and allows one handed operation.

Captive eye keeps the loading close to the spine (thus reducing any loss in strength).

Modified gate reduces chance of cross loading the gate, when used with reach pole (MSRM), when rescuing a casualty.



#### Specifications:

*NB: specifications and colour may change without notice.*

Size: L 238mm, W 114mm

EN Test Mass: N/A

Loading: 22kN major axis

Conformity: EN362:2004/A

Materials: Anodised Aluminium Alloy, Stainless Steel Gate

Weight (kg): 0.50

Industries: Used in all work at height industries and rescue

**All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable**

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: [admin@heightec.com](mailto:admin@heightec.com)

[heightec.com](http://heightec.com)

PDS45

10/02/22