

Scaffold hook, alloy 22kN

CH01

Aluminium alloy hook with wide opening and double action gate.

Features:

- Main body anodised aluminium alloy
- Gate stainless steel
- Double action gate
- Gate opening: 62mm
- Overall Size: L 238mm, W 114mm
- Captive eye

Aluminium Alloy body for reduced weight

Anodised for corrosion protection.

Stainless steel gate for strength

Double action gate is self closing and locking and allows one handed operation.

Captive eye keeps the loading close to the spine (thus reducing any loss in strength).

Also available with modified gate for rescue use - CH01AM

Special gate modification prevents incorrect attachment to the casualty when used with the reach pole - MRM

Without the modification the hook can easily cross load which reduces the strength significantly.



Specifications:

NB: specifications and colour may change without notice.

Size: L 238mm, W 114mm

EN Test Mass:

Loading: 22kN major axis

Conformity: EN 362:2004/A

Materials: Anodised Aluminium Alloy, Stainless Steel

Weight (kg): 0.50

Industries: All industries

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com

[heightec.com](https://www.heightec.com)

PDS1301

10/02/22