

PRODUCT DATA SHEET

SYNC ascender

D44

Integrated chest ascender for Axon or Eclipse/Corona harness combination

Features:

- · Attaches directly to harness
- · Secure, stable and comfortable performs like part of the harness
- Removable
- · X-Cam technology

Attaches directly to the harness, no extra connectors are required. The harness can be opened and closed as normal with a screwlink/karabiner.

Sits tightly against the chest section for efficient ascending.

Attachment points reduce movement to an absolute minimum for optimum comfort and efficiency.

Removable for replacement, no tools are required, simply remove the harness screw link and unhook the SYNC.

X-Cam has a more advanced tooth design than traditional cams and is more suitable for industrial applications as it does not pluck the rope, so reducing rate of rope wear.

- Does not jam, even against knots
- Provides high degree of grip on ropes of varying condition including after rupture of sheath



Patent Pending GB1808077.0

NB: specifications and colour may change without notice.

Specifications:

Size: Rope 10.5 - 12mm

EN Test Mass: 100kg

Loading: 100kg SWL. 1.0kN WLL

Conformity: EN567:2013, EN12841:2006(B)

Materials: Anodised Aluminium Alloy, Stainless Steel Cam, Nylon

Weight (kg): 0.14

Industries: Rope Access

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997